

## DS-D5032F3-1V0S 32 inch FHD Monitor



- 178° ultra-wide view screen.
- 3D noise reduction.
- Low blue light design for eye care.
- Dual interface of HDMI and VGA.
- Support VESA wall mount.

## ▪ Specification

|                            | Model                          | DS-D5032F3-1V0S  |
|----------------------------|--------------------------------|--|
| <b>Display</b>             | Screen Size                    | 32 inch  |
|                            | Active Display Area            | 698.4 (H) mm × 392.85 (V) mm   |
|                            | Resolution                     | 1920 × 1080  |
|                            | Backlight                      | D-LED  |
|                            | Pixel Pitch                    | 0.12125 (H) mm × 0.36375 (V) mm  |
|                            | Brightness                     | 300 cd/m <sup>2</sup>  |
|                            | Viewing Angle                  | 178° (H)/178° (V)  |
|                            | Color Depth                    | 8 bit  |
|                            | Contrast Ratio                 | 4000:1   |
|                            | Response Time                  | 8 ms   |
|                            | Refresh Rate                   | Typ. 60 Hz, Max. 75 Hz   |
|                            | Haze                           | Haze 2%  |
|                            | Reliability                    | 7 × 12 H   |
|                            | Color Gamut                    | 72% NTSC   |
| <b>Interface</b>           | Video & Audio Input            | VGA × 1, HDMI 1.4 × 1, Audio Output × 1  |
|                            | Video & Audio Output           | Speaker (8 Ω 10 W) × 2   |
| <b>Power</b>               | Power Supply                   | 100 to 240 VAC, 50/60 Hz   |
|                            | Power Consumption              | ≤ 48 W   |
|                            | Standby Consumption            | ≤ 0.5 W  |
| <b>Working Environment</b> | Working Temperature            | 0 °C to 40 °C (32 °F to 104 °F)  |
|                            | Working Humidity               | 20% RH to 90% RH (Non-Condensing)  |
|                            | Storage Temperature            | -20 °C to 60 °C (-4 °F to 140 °F)  |
|                            | Storage Humidity               | 10% RH to 90% RH (Non-Condensing)  |
| <b>General</b>             | Casing Material                | Plastic  |
|                            | VESA                           | 100 mm × 100 mm (4 - M6 × 10 mm)   |
|                            | Bezel Width                    | 16.7 mm (top/left/right), 20.5 mm (bottom)   |
|                            | Product Dimensions (W × H × D) | With base: 735.08 (W) mm × 489.16 (H) mm × 207.95 (D) mm (28.94" × 19.26" × 8.19")<br>Without base: 735.08 (W) mm × 433.46 (H) mm × 80.19 (D) mm (28.94" × 17.07" × 3.16")                     |
|                            | Package Dimensions (W × H × D) | 808 (W) mm × 510 (H) mm × 140 (D) mm (31.81" × 20.08" × 5.51")   |
|                            | Net Weight                     | 4.55 kg ± 0.5 kg (10.03 ± 1.10 lb.)  |
|                            | Gross Weight                   | 6.1 kg ± 0.5 kg (13.45 ± 1.10 lb.)   |
|                            | Packing List                   | Monitor × 1, Base component × 1, HDMI cable (1.5 m) × 1, User manual × 1, Multilingual manual × 1, remote control × 1, Base screw × 6, Wall-mount screw × 4                                    |
|                            | Remarks                        | The base is included by default.<br>The product appearance and parameters in this specification may vary from your actual device. Please consult our local sales staff for further information |

