\DomeCam Mini

Wired IP camera

Compatibility	Control panels Hub Hub Plus Hub 2 (2G) Hub 2 (4G) Hub 2 Plus Hub Hybrid (2G) Hub Hybrid (4G) Video recorders NVR
Models	 5 Mp/2.8 mm Resolution up to 2880 × 1620 px Frame rate up to 25 FPS Viewing angle from 100° to 110°
	 5 Mp/4 mm Resolution up to 2880 × 1620 px Frame rate up to 25 FPS Viewing angle from 75° to 85°
	 8 Mp/2.8 mm Resolution up to 3840 × 2160 px Frame rate up to 20 FPS Viewing angle from 100° to 110°
	 8 Mp/4 mm Resolution up to 3840 × 2160 px Frame rate up to 20 FPS Viewing angle from 75° to 85°
Videostream	Video protocol JetSparrow Fast and encrypted peer-to-peer video protocol developed by Ajax Systems.
	Storage NVR Hard drive with a capacity of up to 16 TB (SATA connectivity, 3.5" size). Memory storage device not included. microSD Up to 256 GB. Memory storage device not included.
	Video codec H.265 H.264

	Dynamic ranges True WDR
Communication channel	Ethernet up to 100 Mbps
Key features	Motion detection The camera has software to detect motion in the frame.
	Object detection using AI Humans. Pets. Vehicles.
	Smart IR illumination up to 15 m Automatic adjustment of intensity in real time to avoid overexposure. This allows you to see objects that are far away or too close to the camera in low light conditions.
	Visual verification of Ajax alarms The system allows you to set up a scenario when Ajax detectors activate selected cameras to start recording. The result is immediately sent to the mobile or desktop monitoring app.
	Microphone With the corresponding settings, the camera records sound at the object.
	Audio codec G711-ULAW G711-ALAW G726 G722
Power supply	Power supply unit 12 V= ± 20%, 1 A Up to 15 W of mains power consumption.
	Ethernet port PoE Standard 802.3at
Sabotage protection	mTLS Encrypted connection for data protection.
	Authentication via Cloud Without local access rights.

	Secure Boot
	Protection against firmware spoofing.
	OTA signature verification
	Secure automatic firmware update.
	Privacy
	Access rights distribution for users in mobile
	apps and for monitoring operators in PRO
	Desktop.
Enclosure	Dimensions
	113 × 60 mm 4.45" × 2.36"
	4.45 × 2.36
	Weight
	360 g
	12.70 oz
	Operating temperature range
	from -30 °C to +60 °C
	from -22 °F to 140 °F
	Operating humidity
	up to 90%
	Protection class IP65
Colours	Black White
Osmalsts set	
Complete set	DomeCam Mini Installation template
	Installation kit
	Quick start guide
	24 months